


Art.no. 74604



An easily located reading luminaire for hospital environments with plastic-coated sprung arm for easy cleaning.

Installation Attached to the hospital ward panel, wall, table or IC rail. Brackets ordered separately, please see accessories.

Connection Mains cable 2.0 m, with plug-in transformer 100–240 V, 50/60 Hz. The luminaire is class II.

Design Lamp head of cast aluminium with a lamp assembly consisting of 3 light intensive LEDs for reading light and 3 LEDs for night light. A switch on the top of the lamp head turns the night light on/off while the reading light is dimmable via a switch on the handle. The lamp head can be rotated 360°. The S4 arm consists of a plastic-coated spring arm, followed by rigid aluminium tubing that goes into a friction hinge and ends with a 16 mm mounting pin. S7 does not have a friction hinge, instead it features double plastic-coated spring arms. S8 is identical to S7 but adapted for mounting on beds.

Louvre The louvre is white frosted as standard but can be provided in different finishes on request.

Amalia LED

Amalia 9 P S4, with friction hinge

LIGHT DATA & PERFORMANCE

CCT, K 3000

CRI 90

Energy class, LED module G

ELECTRICITY & ENCLOSURE

System Wattage 9

DIMENSIONS

Weight, kg 1,5