


Art.no. 19136

EAN 7320048158840



A wall-mounted luminaire for lighting mirrors, for example, and that is equally appropriate for hygiene rooms as cloakrooms or corridors.

Installation Horizontally or vertically mounted on a wall. Luminaire with socket outlet only for horizontal installation. Outlet module can be placed on the right or left-hand side.

Connection Cable entries for recessed and surface mounted installation fitted with blanking grommets. Positioning see dimension chart. 3-way terminal block. Luminaire with socket has 4-pole terminal block with possibility of constant voltage to the socket. Luminaire connects via 230 V, built-in driver.

Design Body of white finished polycarbonate. Self-closing cover on the outlet module.

Louvre Diffuser of opal acrylic plastic. The diffuser can be fitted and removed without the use of tools.

Light distribution Direct.

Dimming *e-Sense BrightSwitch* – PIR sensors with lux threshold. Presence control on/off.

Aqua

Direct

DESIGN

Light distribution Direct **Louvre** Opal
Colour White

LIGHT DATA & PERFORMANCE

Lumen output 1773 **lm/W** 123
CCT, K 4000 **CRI** 80
SDCM 3 **Lumen maintenance 50 000 h L88**
Lumen maintenance 75 000 h L83 **Lumen maintenance 100 000 h L77**
Lumen maintenance L70 B50, h **Lumen maintenance L80 B50, h**
 100000 90000
Lumen maintenance L90 B50, h **LED driver, h/max failure %** 50000/10
 40000

Energy class, LED module C

CONTROLS & CONNECTIVITY

Driver brand Tridonic

ELECTRICITY & ENCLOSURE

Rated supply voltage, V 220-240 **Mains frequency, Hz** 50, 60
Protective class 1 **IP rating** 44
System Wattage 14 **Min. ambient temperature, °C** -20
Max. ambient temperature, °C 25 **MCB B10A, pcs** 50
MCB B16A 80 **MCB C10A** 50
MCB C16A 80 **Surge protection CM, kV/kA** 2
Surge protection DM, kV/kA 1 **Power factor, 100 %** 0.95

DIMENSIONS

Length, mm 599 **Width, mm** 54
Height, mm 55 **Weight, kg** 0.6